

Hot Water Generators:-

Oil / Gas fired:-

PROFILE

AQUATHERM is a Fully Automatic Oil / Gas Generator.
It is available in Vertical & Horizontal Type.
Range- 15,000 kcal/Hr. to 5,000,000 kcal/Hr.
Burner Control - Single Stage / Two Stage / Stepless Modulating.
Temperature Range 90°C at atmospheric pressure / 140 & 180°C Pressurized.

DESIGN FEATURES

- High Efficiency—Less Fuel consumption.
- Single Button Start / Stop with Automatic Control with Safety features.
- Noiseless operation with monobloc Burner .
- No water treatment required when used with Calorifier.
- Smokeless combustion. Low Pollutants.
- No explosion hazards due to coil design.



Electrical type:-

PROFILE

AQUATHERM-E is a Fully Automatic Electrical Hot Water Generator.
It is available in Vertical & Horizontal Type.
Range- 10,000 kcal/Hr. to 400,000 kcal/Hr.
Burner Control - Multi Stage / Stepless Modulating.
Temperature Range 90°C at atmospheric pressure / 140 & 180°C Pressurized.

DESIGN FEATURES

- High Efficiency
- Single Button Start / Stop with Automatic Control with Safety features.
- Noiseless operation with monobloc Burner .
- No water treatment required when used with Calorifier.
- Smokeless combustion. Low Pollutants.
- No explosion hazards due to coil design.



Solid Fuel (Wood / Coal) fired:-

PROFILE

AQUATHERM-SF is a Solid Fuel Fired Hot Water Generator.
It is available in Vertical & Horizontal Smoke Tube Type.
Range- 10,000 kcal/Hr. to 400,000 kcal/Hr.
Temperature Range 90°C at atmospheric pressure.
140 & 180°C Pressurized type.

DESIGN FEATURES

- Most Economical in operating cost.
- No water treatment required when used with Calorifier.

